

# Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 12

Fa Deospray Body & Sense Empowering

SDS No.: 739604 V001.0 Revision: 22.02.2023 printing date: 10.05.2023

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Fa Deospray Body & Sense Empowering

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Deo Spray, Aerosol

#### 1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA Düsseldorf Germany Henkelstr. 67 40191 Düsseldorf +49 211-797-0 Phone:

#### E-mail address of person responsible for Safety Data Sheet:

Henkel Consumer Brands, e-mail: Andrea.Saettler@henkel.com

#### 1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases. Further information is available at Poison Control Centers.

## **SECTION 2: Hazards identification**


#### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008 (CLP):

Aerosol Category 1 Extremely flammable aerosol. Pressurized container: May burst if heated.

#### 2.2. Label elements (CLP)

Hazard pictogram:



## 2.3. Other hazards

Following substances are present in a concentration  $\geq$  the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration  $\geq$  the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

## **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

#### 3.2. Mixtures

#### Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M- factors and ATEs	Add. Information
Butane, n- (< 0.1 % butadiene) 106-97-8 203-448-7 01-2119474691-32	>= 50-< 70 %	Press. Gas H280 Flam. Gas 1A, H220		
Ethanol denatured 64-17-5 200-578-6 01-2119457610-43	>= 20-< 30 %	Flam. Liq. 2, H225 Eye Irrit. 2, H319	Eye Irrit. 2; H319; C > 50 %	
Propane 74-98-6 200-827-9 01-2119486944-21	>= 1-< 10 %	Flam. Gas 1A, H220 Press. Gas H280		
Isobutane 75-28-5 200-857-2 01-2119485395-27	>= 1-< 10 %	Flam. Gas 1A, H220 Press. Gas Liquef. Gas, H280		

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

General information: In case of adverse health effects seek medical advice. Remove casualty immediately from danger zone. Take off immediately all contaminated clothing.

Inhalation: Move to fresh air.

Skin contact: Rinse with water. Take off all clothing contaminated by the product.

Eye contact: Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion: Rinse the mouth. Drink 1-2 glasses of water.

## **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media: All common extinguishing agents are suitable.

Extinguishing media which must not be used for safety reasons: None known

#### 5.2. Special hazards arising from the substance or mixture The release of following substances is possible in case of fire:

carbon oxides. nitrogen oxides

#### **5.3.** Advice for firefighters

Wear self-contained breathing apparatus. Wear protective equipment.

#### Additional information:

Dispose of combustion residues and contaminated fire-fighting water in accordance with statutory regulations. Collect contaminated fire fighting water separately. It must not enter drains. In case of fire, keep containers cool with water spray.

## **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Take great care to avoid inhalation of the aerosol.

#### **6.2.** Environmental precautions

Do not allow to enter drainage system, surface or ground water of not diluted product. Do not dispose of in wastepaper bin or trash-can.

#### 6.3. Methods and material for containment and cleaning up

Dilute small quantities with large amount of water and rinse.

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Handling advice: No particular measures required.

Fire and explosion protection information: Take measures to prevent the build-up of electrostatic charges. Do not spray onto flame or red-hot objects. Keep away from sources of ignition - no smoking.

Hygiene measures:

Do not eat, drink or smoke while working. Immediately remove soiled or soaked clothing. Wash hands before work breaks and after finishing work. Keep away from food, beverages and animal feed.

**7.2. Conditions for safe storage, including any incompatibilities** Store in sealed original container protected against moisture. For aerosols: protect from direct sunshine and temperatures above 50°C. Store far from foodstuffs.

**7.3. Specific end use(s)** Deo Spray, Aerosol

## **SECTION 8: Exposure controls/personal protection**

#### Only relevant for professional/industrial use

#### 8.1. Control parameters

Valid for

Germany

Ingredient [Regulated substance]	ррт	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Remarks
Butane 106-97-8	1.000	2.400	Exposure limit(s):	4	TRGS 900
Butane 106-97-8			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Ethanol 64-17-5			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Ethanol 64-17-5	200	380	Exposure limit(s):	4 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Propane 74-98-6	1.000	1.800	Exposure limit(s):	4	TRGS 900
Propane 74-98-6			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Isobutane 75-28-5			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Isobutane 75-28-5	1.000	2.400	Exposure limit(s):	4	TRGS 900

#### 8.2. Exposure controls

Engineering controls: Ensure good ventilation/suction at the workplace.

Respiratory protection: When processing in open systems with aerosol formation wear suitable respiratory protection to avoid inhalation of aerosol particles.

Hand protection: Not needed.

Eye protection: No special measures required if used properly.

Skin protection: Not needed.

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Appearance

aerosol low viscosity colourless/light yellow

Odor

Physical state Melting point Initial boiling point Flammability aromatic, citric, floral aerosol Currently under determination Currently under determination Currently under determination Explosive limits Flash point Auto-ignition temperature Decomposition temperature pH Viscosity (kinematic) Solubility (qualitative) (20 °C (68 °F); Solvent: Water) Partition coefficient: n-octanol/water Vapour pressure Density ()

Relative vapour density: Particle characteristics

#### 9.2. Other information

Other information not applicable for this product

Currently under determination Not applicable Currently under determination Currently under determination Currently under determination Currently under determination Soluble

Currently under determination Currently under determination 0,607 g/cm3 Density - calculated::245200

Currently under determination Currently under determination

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

None if used for intended purpose.

# **10.2. Chemical stability** None known.

#### 10.3. Possibility of hazardous reactions

See section reactivity None known.

#### **10.4. Conditions to avoid** Keep away from sources of ignition and naked flames.

Reep away nom sources of ignition and naked i

# 10.5. Incompatible materials

None known.

#### 10.6. Hazardous decomposition products

None known.

## **SECTION 11: Toxicological information**

#### General toxicological information:

The present product is a chemical preparation within the meaning of the chemicals act. The following evaluation has been made on the basis of the toxicological data and content by weight of the individual ingredients. No information exists about acute toxic, irritative or otherwise harmful effects caused by the product.

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Ethanol denatured 64-17-5	LD50	10.470 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

#### Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Ethanol denatured 64-17-5	LD50	> 2.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)

## Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Butane, n- (< 0.1 % butadiene) 106-97-8	LC50	274200 ppm	gas	4 h	rat	not specified
Ethanol denatured 64-17-5	LC50	124,7 mg/l	vapour	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
Propane 74-98-6	LC50	> 800000 ppm	gas	15 min	rat	not specified
Isobutane 75-28-5	LC50	260200 ppm	gas	4 h	mouse	not specified

#### Skin corrosion/irritation:

No data available.

## Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Ethanol denatured 64-17-5	irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Ethanol denatured 64-17-5	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

## Respiratory or skin sensitization:

No data available.

## Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result	Type of study /	Metabolic	Species	Method
CAS-No.		Route of	activation /	-	
		administration	Exposure time		
Butane, n- (< 0.1 %	negative	bacterial reverse	with and without		OECD Guideline 471
butadiene)	_	mutation assay (e.g			(Bacterial Reverse Mutation
106-97-8		Ames test)			Assay)
Butane, n- (< 0.1 %	negative	in vitro mammalian	with and without		OECD Guideline 473 (In vitro
butadiene)	_	chromosome			Mammalian Chromosome
106-97-8		aberration test			Aberration Test)
Propane	negative	bacterial reverse	with and without		OECD Guideline 471
74-98-6	_	mutation assay (e.g			(Bacterial Reverse Mutation
		Ames test)			Assay)
Propane	negative	in vitro mammalian	with and without		OECD Guideline 473 (In vitro
74-98-6	_	chromosome			Mammalian Chromosome
		aberration test			Aberration Test)
Isobutane	negative	bacterial reverse	with and without		OECD Guideline 471
75-28-5	_	mutation assay (e.g			(Bacterial Reverse Mutation
		Ames test)			Assay)
Isobutane	negative	in vitro mammalian	with and without		OECD Guideline 473 (In vitro
75-28-5		chromosome			Mammalian Chromosome
		aberration test			Aberration Test)
Butane, n- (< 0.1 %	negative	inhalation: gas		rat	OECD Guideline 474
butadiene)					(Mammalian Erythrocyte
106-97-8					Micronucleus Test)
Propane	negative			Drosophila	not specified
74-98-6				melanogaster	
Propane	negative	inhalation: gas		rat	OECD Guideline 474
74-98-6					(Mammalian Erythrocyte
					Micronucleus Test)
Isobutane	negative	oral: feed		Drosophila	not specified
75-28-5				melanogaster	
Isobutane	negative	inhalation: gas		rat	OECD Guideline 474
75-28-5					(Mammalian Erythrocyte
					Micronucleus Test)

## Carcinogenicity

No data available.

## **Reproductive toxicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Butane, n- (< 0.1 % butadiene) 106-97-8	NOAEL P 21,4 mg/l NOAEL F1 21,4 mg/l	screening	inhalation: gas	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Propane 74-98-6	NOAEL P 21,6 mg/l NOAEL F1 21,6 mg/l	screening	inhalation: gas	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Isobutane 75-28-5	NOAEL P 21,4 mg/l NOAEL F1 21,4 mg/l	screening	inhalation: gas	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

## STOT-single exposure:

No data available.

## STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Butane, n- (< 0.1 % butadiene) 106-97-8		inhalation: gas	28 d 6 h/d	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Propane 74-98-6		inhalation: gas	28 d 6 h/d, 7 d/w	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Isobutane 75-28-5	NOAEL 9000 ppm	inhalation: gas	28 d 6 h/d, 7 d/w	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

## Aspiration hazard:

No data available.

## 11.2 Information on other hazards

not applicable

## **SECTION 12: Ecological information**

#### General ecological information:

The ecological evaluation of the product is based on data from the raw material and/or comparable substances.

## 12.1. Toxicity

#### Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type		_	_	
Butane, n- (< 0.1 % butadiene)	LC50	27,98 mg/l	96 h		not specified
106-97-8					
Ethanol denatured	LC50	> 12.000 - 16.000 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish,
64-17-5					Acute Toxicity Test)

#### Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Butane, n- (< 0.1 % butadiene) 106-97-8	EC50	14,22 mg/l	48 h		not specified
	EC50	> 100 mg/l	24 h	I G	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

#### Chronic toxicity to aquatic invertebrates

No data available.

#### Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Butane, n- (< 0.1 % butadiene) 106-97-8	EC50	7,71 mg/l	96 h		not specified
Ethanol denatured 64-17-5	EC50	> 100 mg/l	24 h	15	OECD Guideline 201 (Alga, Growth Inhibition Test)

#### Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Ethanol denatured 64-17-5	IC50	> 1.000 mg/l	3 h		OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

#### 12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Butane, n- (< 0.1 % butadiene) 106-97-8	readily biodegradable	aerobic	> 60 %	28 d	OECD 301 A - F
Ethanol denatured 64-17-5	readily biodegradable	aerobic	> 70 %	5 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Propane 74-98-6	readily biodegradable	aerobic	> 60 %	28 d	OECD 301 A - F
Isobutane 75-28-5	readily biodegradable	aerobic	71,43 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

## 12.3. Bioaccumulative potential

No data available.

## 12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
Butane, n- (< 0.1 % butadiene) 106-97-8	2,31	20 °C	other (measured)
Isobutane 75-28-5	2,88	20 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

## 12.5. Results of PBT and vPvB assessment

Hazardous substances	PBT / vPvB
CAS-No.	
Butane, n- (< 0.1 % butadiene)	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
106-97-8	Bioaccumulative (vPvB) criteria.
Ethanol denatured	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
64-17-5	Bioaccumulative (vPvB) criteria.
Propane	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
74-98-6	Bioaccumulative (vPvB) criteria.
Isobutane	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
75-28-5	Bioaccumulative (vPvB) criteria.

## 12.6. Endocrine disrupting properties

not applicable

## 12.7. Other adverse effects

No data available.

# **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

Product disposal:

Consider national regulations.

# **SECTION 14: Transport information**

## 14.1. UN number or ID number

ADR	1950
RID	1950
ADN	1950
IMDG	1950
IATA	1950

## 14.2. UN proper shipping name

ADR	AEROSOLS
RID	AEROSOLS
ADN	AEROSOLS
IMDG	AEROSOLS
IATA	Aerosols, flammable

## 14.3. Transport hazard class(es)

2.1
2.1
2.1
2.1
2.1

## 14.4. Packing group

ADR RID ADN IMDG IATA

#### 14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

## 14.6. Special precautions for user

not applicable
Tunnelcode: (D)
not applicable
not applicable
not applicable
not applicable

## 14.7. Maritime transport in bulk according to IMO instruments

not applicable

## **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations/information (Germany):

WGK:	WGK 1: slightly hazardous to water (Germany. Ordinance on Facilities Handling Substances that are Hazardous to Water, ((AwSV of 21 April 2017),
	UBA, BAnz AT), as amended )
	Classification in conformity with the calculation method
Storage class according to TRGS 510:	2B

#### 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

## **SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H220 Extremely flammable gas.H225 Highly flammable liquid and vapour.H280 Contains gas under pressure; may explode if heated.H319 Causes serious eye irritation.

#### Further information:

This information is not related to the use of the product, it is based on our current level of knowledge.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very
	bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria